

TRANSPO

POWER DIODES



WAIglobal 

Part #	Type	Cup Dim.	Polarity	Voltage	Amperage	Avalanche Voltage	Overall device height	Plating	Pictures
32-8308	Block	-	P	200	40	-	-	Tin	
32-8309	Block	-	N	200	40	-	-	Tin	
32-8306	Block	-	P	200	35	-	-	Tin	
32-8307	Block	-	N	200	35	-	-	Tin	
32-8300	Block	-	P	200	30	-	-	Tin	
32-8301	Block	-	N	200	30	-	-	Tin	
32-1060110	Bosch	13mm	P	-	60	20-24	30.00 ± 0.5mm	Nickel	
32-1060111	Bosch	13mm	N	-	60	20-24	30.00 ± 0.5mm	Nickel	
32-1060103	Bosch	13mm	N	-	60	24-31	31.10 ± 0.5mm	Nickel	
32-1060105	Bosch	13mm	N	-	60	24-29	32.50 ± 0.5mm	Nickel	
32-1060901	Bosch	13mm	N	300	60	-	22.70 ± 0.5mm	Nickel	
32-1060912	Bosch	13mm	P	300	60	-	32.20 ± 0.5mm	Tin	
32-1060913	Bosch	13mm	N	300	60	-	32.20 ± 0.5mm	Tin	
32-1050100	Bosch	13mm	P	-	50	20-24	28.00 ± 0.5mm	Nickel	
32-1050101	Bosch	13mm	N	-	50	20-24	28.00 ± 0.5mm	Nickel	
32-1050900	Bosch	13mm	P	300	50	-	30.00 ± 0.5mm	Nickel	
32-1050901	Bosch	13mm	N	300	50	-	30.00 ± 0.5mm	Nickel	
32-1040900	Bosch	13mm	P	300	40	-	30.00 ± 0.5mm	Nickel	
32-1040901	Bosch	13mm	N	300	40	-	30.00 ± 0.5mm	Nickel	
32-1040912	Bosch	13mm	P	300	40	-	30.00 ± 0.5mm	Tin (Solder Dip)	
32-1040913	Bosch	13mm	N	300	40	-	30.00 ± 0.5mm	Tin (Solder Dip)	
32-1040920	Bosch	13mm	P	300	40	-	18.50 ± 0.5mm	Tin (Solder Dip)	
32-1040921	Bosch	13mm	N	300	40	-	24.50 ± 0.5mm	Tin (Solder Dip)	
32-727	Button	8.5mm	N	100	50	-	24.50 ± 0.5mm	Tin	
32-728	Button	8.5mm	P	100	50	-	28.80 ± 0.5mm	Tin	
32-735	Button	8.5mm	-	200	50	-	-	Tin	
32-779	Button	10mm	-	200	50	-	-	Tin	
32-725	Button	8.5mm	N	100	25	-	31.70 ± 0.5mm	Tin	
32-726	Button	8.5mm	P	100	25	-	24.10 ± 0.5mm	Tin	
32-734	Button	8.5mm	-	200	25	-	-	Tin	
32-8927	Dish	9.5	N	200	30	-	25.00 ± 0.5mm	Nickel	
32-8927-10	Dish	9.5	N	200	30	-	25.00 ± 0.5mm	Tin	
32-8928	Dish	9.5	P	200	30	-	25.00 ± 0.5mm	Nickel	
32-8928-10	Dish	9.5	P	200	30	-	25.00 ± 0.5mm	Tin	
32-8917	Dish	9.5	N	200	30	-	25.00 ± 0.5mm	Nickel	
32-8918	Dish	9.5	P	200	30	-	25.00 ± 0.5mm	Nickel	
32-8909	Dish	8.4	N	200	20	-	25.00 ± 0.5mm	Nickel	
32-8910	Dish	8.4	P	200	20	-	25.00 ± 0.5mm	Nickel	
32-8106	Hitachi	11.5mm	N	100	50	-	21.30 ± 0.5mm	Nickel	
32-8107	Hitachi	11.5mm	P	100	50	-	21.30 ± 0.5mm	Nickel	
32-8108	Hitachi	11.5mm	N	-	50	24-32	21.40 ± 0.5mm	Nickel	
32-8109	Hitachi	11.5mm	P	-	50	24-32	21.40 ± 0.5mm	Nickel	

Diodes

Part #	Type	Cup Dim.	Polarity	Voltage	Amperage	Avalanche Voltage	Overall device height	Plating	Pictures
32-8104	Hitachi	11.5mm	N	200	40	-	21.10 ± 0.5mm	Nickel	
32-8105	Hitachi	11.5mm	P	200	40	-	21.10 ± 0.5mm	Nickel	
8640-3	Hitachi	11.5mm	P	200	40	-	21.30 ± 0.5mm	Nickel	
8641-3	Hitachi	11.5mm	N	200	40	-	21.30 ± 0.5mm	Nickel	
32-8102	Hitachi	11.5mm	N	100	30	-	21.20 ± 0.5mm	Nickel	
32-8103	Hitachi	11.5mm	P	100	30	-	21.20 ± 0.5mm	Nickel	
32-7100	Motorola	1/2"	N	-	70	24-32	22.00 ± 0.5mm	Tin	
32-7101	Motorola	1/2"	P	-	70	24-32	22.00 ± 0.5mm	Tin	
32-787	Motorola	1/2"	N	200	70	-	22.10 ± 0.5mm	Tin	
32-788	Motorola	1/2"	P	200	70	-	22.10 ± 0.5mm	Tin	
32-502	Motorola	1/2"	N	200	50	-	22.10 ± 0.5mm	Tin	
32-503	Motorola	1/2"	N	200	50	-	22.10 ± 0.5mm	Tin	
32-754	Motorola	1/2"	N	200	50	-	22.00 ± 0.5mm	Tin	
32-755	Motorola	1/2"	P	200	50	-	22.00 ± 0.5mm	Tin	
32-102	Motorola	1/2"	N	200	35	-	18.60 ± 0.5mm	Tin	
32-103	Motorola	1/2"	P	200	35	-	18.60 ± 0.5mm	Tin	
32-306	Motorola	1/2"	N	200	35	-	22.60 ± 0.5mm	Tin	
32-307	Motorola	1/2"	P	200	35	-	22.60 ± 0.5mm	Tin	
32-762	Motorola	1/2"	P	400	35	-	35.50 ± 0.5mm	Tin	
32-773	Motorola	1/2"	N	200	35	-	35.70 ± 0.5mm	Tin	
32-774	Motorola	1/2"	P	200	35	-	35.70 ± 0.5mm	Tin	
32-107	Motorola	1/2"	N	100	25	-	20.00 ± 0.5mm	Tin	
32-108	Motorola	1/2"	P	200	25	-	20.00 ± 0.5mm	Tin	
32-748	Motorola	1/2"	N	200	25	-	35.80 ± 0.5mm	Tin	
32-749	Motorola	1/2"	P	200	25	-	35.80 ± 0.5mm	Tin	
8752K	Motorola Diode Kit	1/2"	P	200	50	-	-	Tin	
8753K	Motorola Diode Kit	1/2"	N	200	50	-	-	Tin	
867D	Stud	-	N	200	150	-	-	Tin	
1120	Stud	-	P	200	70	-	-	Tin	
1120R	Stud	-	N	200	70	-	-	Tin	
32-783	Tin Can	5/16"	N	200	50	-	26.50 ± 0.5mm	Tin	
32-784	Tin Can	5/16"	P	200	50	-	26.50 ± 0.5mm	Tin	
32-721	Tin Can	5/16"	N	200	25	-	26.60 ± 0.5mm	Tin	
32-722	Tin Can	5/16"	P	200	25	-	26.60 ± 0.5mm	Tin	
32-723	Tin Can	5/16"	N	200	25	-	19.50 ± 0.5mm	Tin	
32-724	Tin Can	5/16"	P	200	25	-	19.50 ± 0.5mm	Tin	
8030	Trio	-	-	200	3	-	62.00 ± 0.5mm	Tin	
8025	Trio	-	-	200	2.5	-	62.00 ± 0.5mm	Tin	
8015	Trio	-	-	200	1.5	-	58.00 ± 0.5mm	Tin	
8010	Trio	-	-	200	1	-	62.40 ± 0.5mm	Tin	

TRANSPO

POWER DIODES



Member of:

AAIA[®]
Automotive Aftermarket
Industry Association



USA

WAIglobal USA

411 Eagleview Blvd., Suite 100,
Exton, PA 19341
Tel: 484.875.6600
Toll Free: 800.877.3340
Fax: 800.948.6121

CANADA

Montréal

4711 Boul. Couture
Montréal (St-Léonard),
Québec, H1R 3H7
Tel: 514.324.7922
Toll Free: 800.661.2962
Fax: 514.328.1535

Toronto

34 Alex Avenue
Vaughan, Ontario
L4L 5X1
Tel: 416.740.9200
Toll Free: 800.387.2807
Fax: 416.740.5348

EUROPE

WAI Europe b.v.

Klappolder 225
2665 MR Bleiswijk
The Netherlands
Tel: 31(0)10.524.1980
Fax: 31(0)10.524.1981

CHINA

Transpo Electronics, Shanghai, LTD

Building No. 32 215 De Bao Rd
Wai Gao Qiao Free Trade Zone
Pudong, Shanghai 200131
Peoples Republic of China
Tel: 86.21.5048.2700
Fax: 86.21.5048.2722

BRASIL

WAIglobal Brazil Ltda

Av. Coronel Marcos Konder,
1207-Sala 70
88.301-303, Itajai-SC
Fone/Fax: (47)3046.1600

WAIglobal 

www.waiglobal.com